USB Wireless LAN - Important Notice

Installing the USB Wireless LAN Software Under Windows 98

When the USB Wireless LAN is the only network adapter installed on your system and you installed the NetBEUI protocol, the computer may hang during the boot phase.

To avoid this situation you can either uninstall the NetBEUI protocol or install Dial-Up Adapter.

To remove the NetBEUI protocol:

1   Click ➪ **Start** ➪ **Settings** ➪ **Control Panel**.
2   Double-click the **Network** icon.
3   Select the **NetBEUI** protocol and click **Remove**.
4   Click **OK**. Click **Yes** when you are prompted to restart your system.

To install Dial-Up Adapter:

1   Click **Start** ➪ **Settings** ➪ **Control Panel**.
2   Double-click the **Network** icon.
3   Click the **Add** button.
4   From the **Select Network Component Type** dialog box select **Adapter** and then click the **Add** button.
5   From the left pane of the **Select Network adapter** dialog box select **Microsoft** and then **Dial-Up Adapter** in the right pane.
6   Click **OK** and close all dialog boxes. Click **Yes** when you are prompted to restart your system.

HP Support

You can get help solving problems with HP accessories from the following HP support Web sites:

www.hp.com/go/briosupport

www.hp.com/go/vectrasupport

www.hp.com/go/kayaksupport

www.hp.com/go/e-pcsupport